

# Direct Hygiene Supplies

Sales Free Phone 0800 612 9688



Product ID: MCM08A - DUALFLOW hand dryer M08A White

Dualflow: WHITE

Elegant and innovative design. Dries hands in only 10 to 15 seconds. It activates automatically when putting hands in the drying area. High speed universal brush motor. Suitable for medium and high traffic facilities. Normally goes along with a soap dispenser.

Dualflow Technical Specifications

Voltage 100-120, 208, 220-240 V

Frequency 50/60 Hz

Electrical isolation Class I

Weight 6,9 Kg

Effective airflow 61-98 m<sup>3</sup>/h 1012-1632 l/min

Nominal airflow 73-118 m<sup>3</sup>/h 1215-3200 l/min

Air velocity 90-180 Km/h

Total power 1.150 W

Motor power 250 W

Heating element power 900 W

Consumption 4.8 A (240 V) 9.5 A (120 V) A

RPM 3.800 - 8200

Air temperature(10 cm distance / 21 °C) 41 - 44 °C

Noise level (at 2 m) 64-74 dB

Protection level IP23

Operation

Place hands inside the hand dryer. An electronic system based on infrared sensors will detect them and the unit

will start automatically working and go on with no interruption during 23 seconds. When hands are removed the dryer will stop.

#### Specification

Surface mounted and CE/UL compliant hand dryer shall be manufactured with high-impact 3 mm thick ABS cover, bright. The dryer should be 220-240V voltage. The dryer shall be activated through an infrared electronic sensor when putting hands inside the dryer and shall automatically turn off after hands are removed. High speed universal brush motor should be 1760 W total power, 30000 rpm, F class. The dryer shall have a total power of 1760 Watts with a consumption of 8 A (at 220 V). Noise level should be 70 dB at 2 m distance. Protection level against water splashes should be rating IP33. Overall dimensions shall be 617 x 300 x 195 mm. Unit shall CE marked and comply with electrical safety directives 73/23/CEE & 93/68/CEE and electro-magnetic compatibility directives 89/336/CEE & 92/31/CEE.

#### N° dryers to be fitted:

In toilet areas with a normal frequency of use and only one wash-basin: 1 dryer.  
In toilet areas with a normal frequency of use and more than one wash-basin: 1 dryer for each 2 wash-basins.  
1 row of 4 wash basins: 2 dryers; 1 row of 6 wash basins: 3 dryers; 1 row of 8 wash basins: 4 dryers.  
In toilet areas with high traffic and more than one wash-basin: 2 dryers for each 3 wash-basins.  
1 row of 4 wash basins: 3 dryers; 1 row of 6 wash basins: 4 dryers; 1 row of 8 wash basins: 5 dryers.

#### Ideal Location:

Between the wash-basin and exit. It is not recommended to install dryer between wash-basins, next to urinals, lavatories and showers. If installing automatic dryers over marble surface or ledge, the minimum distance from the dryer to the ledge must be 400 mm. It is recommended that hand dryers be distributed throughout the washroom area to avoid overcrowding.

#### Recommended heights

Distance from the floor See picture diagram

[Click here for the Dualflow Technical Sheet](#)

**Our Price: 450.00 GBP + VAT**

Direct Hygiene Supplies is a trading division of:  
Direct Hygiene Limited  
Unit 20, Longton Business Park, Station Road  
Little Hoole, Preston, Lancashire, PR4 5LE  
Telephone: 0870 766 9909 Facsimile: 0870 766 5119

**Sales FREE Phone 0800 612 9688 Website: [www.handdryersuk.com](http://www.handdryersuk.com)**