

Direct Hygiene Supplies

Sales Free Phone 0800 612 9688



Product ID: MCM04A - SMARTFLOW hand dryer M04A

M04A Hand dryer Smartflow sensor operated white ABS

- Hand dryer, ABS cover, 3 mm (1/8") thick.
- White finish.
- Drying time 39 seconds.
- Sensor operated.
- Total power: 1.100 W.
- Size: 258 x 145 x 138 mm (10-3/16" x 5-11/16" x 5-3/8").

General Description

- Warm air hand dryer.
- Sensor operated by hand approximation.
- Suitable for medium traffic facilities.
- Compact, small size.
- Highest durability in its class.
- It normally goes along with a soap dispenser

Components and Materials

- White ABS thermoplastic one-piece cover, 3 mm thick. Cover fixed to the base by means of 2 metal sheet screws.
- Thermoplastic PP + talcum base, with 4 Ø 6 mm holes for wall mounting (screws and wall plugs are provided).
- Universal brush motor, 15.000 rpm, class B, includes a self-resetable thermal cut-off at 100 °C.
- PP UL94-V0 helicoidal fan wheel.
- Waved Ni-Cr wire heating element that incorporates a self-resetable thermal cut-off at 95 °C.
- Adjustable (5-20 cm) IR electronic detection sensor.

- IR Sensor with PC viewing screen.

Technical Specifications

Voltage 220-240 V

Frequency 50/60 Hz

Electrical isolation Class II

Dimensions 258x 145x 138 mm

Weight 1,2 Kg

Effective airflow 96 m³/h / 1.600 l/min

Nominal airflow 110 m³/h 1.833 l/min

Air velocity 85 Km/h

Total power 1.100 W

Motor power 150 W

Heating element power 950 W

Consumption 4,8 A

RPM 15.000

Air temperature(10 cm distance / 21 °C) 47 °C

Noise level (at 2 m) 60 dB

Protection level IP23

Operation

Place the hands under the air outlet grill. The dryer will start automatically, and go on with no interruption as long as the hands be kept in the detection range of the sensor. The appliance will stop 2 seconds after the hands are removed from the airflow

Specification

Surface mounted hand dryer shall be fabricated with one-piece 3 mm thick high-quality white ABS thermoplastic fixed to the base by means base of 2 metal sheet screws. The back base shall be thermoplastic PP + talcum base, with 4 Ø 6 mm holes for wall mounting (screws and wall plugs are provided). The dryer shall be activated through an adjustable (5-20 cm) IR electronic detection sensor and shall automatically turn off two second after hands are removed. Sensor should have a PC viewing screen. Shall have an universal brush motor, 15.000 rpm, class B, including a self-resetable thermal cut-off at 100 °C. The waved Ni-Cr wire heating element shall incorporates a self-resetable thermal cut-off at 95 °C. The fan wheel shall be PP UL94-V0 helicoidal. Dryer shall deliver 96 m³/h of air at 47 °C and 85 Km/h velocity during user controlled drying time. The dryer shall have a total power of 1.100 Watts with a consumption of 4,8 A. Noise level should be 60 dB at 2 m distance. Protection level against water splashes should be rating IP23. Overall dimensions shall be 258 x 145 x 138 mm. Unit should be VDE approved and CE marked and comply with electrical safety directives 73/23/CEE & 93/68/CEE and electro-magnetic compatibility directives 89/336/CEE & 92/31/CEE.

Surface mounted hand dryer shall be model M04A sensor operated white ABS thermoplastic cover, manufactured by Mediclinics S.A., C/ Industria 54, E-08025 Barcelona, Spain.

Nº dryers to be fitted:

In toilet areas with a normal frequency of use and only one wash-basin: 1 dryer.

In toilet areas with a normal frequency of use and more than one wash-basin: 1 dryer for each 2 wash-basins.

1 row of 4 wash basins: 2 dryers; 1 row of 6 wash basins: 3 dryers; 1 row of 8 wash basins: 4 dryers.

In toilet areas with high traffic and more than one wash-basin: 2 dryers for each 3 wash-basins.

1 row of 4 wash basins: 3 dryers; 1 row of 6 wash basins: 4 dryers; 1 row of 8 wash basins: 5 dryers.

Ideal Location:

Between the wash-basin and exit. It is not recommended to install dryer between wash-basins, next to

urinals, lavatories and showers. If installing automatic dryers over marble surface or ledge, the minimum distance from the dryer to the ledge must be 400 mm. It is recommended that hand dryers be distributed throughout the washroom area to avoid overcrowding

For recommended height from floor see diagram

[Click here for the Smartflow Technical Sheet](#)

Our Price: 85.00 GBP + VAT

Direct Hygiene Supplies is a trading division of:
Direct Hygiene Limited
Unit 20, Longton Business Park, Station Road
Little Hoole, Preston, Lancashire, PR4 5LE
Telephone: 0870 766 9909 Facsimile: 0870 766 5119

Sales FREE Phone 0800 612 9688 Website: www.handdryersuk.com